

BFI AFFF Fire Extinguishers



Easy extinguishing of class A fires

STORE PRESSURE TYPE		CARTRIDGE TYPE		
Code No.	FEX303-SS-450-EN	FEX304-SS-500-EN	FEX305-SS-450-EN	FEX306-SS-135-EN
Capacity:	45L	135L	45L	135L
Propellant	Nitrogen		0.6kg CO2 Cartridge	
Fire Rating	A IV B			
Operating Temperature:	+5°C to 60°C			
Test Pressure:	25 Bar			
Operating Pressure:	14 Bar			
Approx. Discharge Time:	165-185 secs	16-17 mins	180-200 secs	14-15 mins
Approx. Full Weight:	90kg	205kg	90kg	210kg
Approx. Size (WxLxH mm)	560x700x1020	650x830x1570	560x700x1020	650x900x1570
Approx. Throw Range	12m			

Uses and applications

- Class A fires
- Class B fires
- Class E fires

Australian standard hose reel features

- High fire ratings
- Units come with wheeled trolleys
- One-year warranty

The mobile extinguisher range is deployed in high risk areas where there is a lack of additional fire fighting cover. The range is easily used by one person. Mobile units are available with AFFF foam, multi-purpose ABE powder standard, and carbon dioxide CO2.

BFI'S Foam Type Mobile Fire extinguishers are manufactured using stainless steel cylinders.

Other size mobile units available on request