

BFI ABE Mobile Fire Extinguishers



STORE PRESSURE TYPE		CARTRIDGE TYPE		
Code No.	FEX220-MS-250-EN	FEX221-MS-500-EN	FEX225-MS-250-EN	FEX222-MS-500-EN
Capacity:	25kg	50kg	25kg	50kg
Propellant	Nitrogen	Nitrogen	0.28kg Nitrogen Cartridge	0.28kg Nitrogen Cartridge
Fire Rating	A II B C			
Operating Temperature:	-30°C to 60°C			
Test Pressure:	25 Bar			
Operating Pressure:	14 Bar			
Approx. Discharge Time:	18-25 secs	33-40 secs	16-24 secs	43-57 secs
Approx. Full Weight:	55kg	95kg	60kg	106kg
Approx. Size (WxLxH mm)	460x550x940	560x700x1020	460x550x940	560x750x1026
Approx. Throw Range	10m			

Uses and applications

- Class A fires
- Class B fires
- Class E fires

Australian standard hose reel features

- High fire ratings
- Units come with wheeled trolleys
- One-year warranty

The mobile extinguisher range is deployed in high risk areas where there is a lack of additional fire fighting cover. The range is easily used by one person. Mobile units are available with AFFF foam, multi-purpose ABE powder standard, and carbon dioxide CO₂.