

Certified by SAI Global to AS1221 and with years of development behind it, BFI's 19mm x 36m Swing Arm Fire Hose Reel is widely regarded as one of the best and most reliable Hose Reels available on the Australian Market. Swing Arm Hose Reels are mounted so that they swing out and allow the fire hose to unspool in the direction the user is pulling it. Making for a smoother reel operation.

Features

- Australian Standard Certification by SAI Global (5 Ticks)
- High quality construction
- Option of finishes dependent on application
- Easy to install and maintain
- After sales service and ongoing technical support
- Guide Arm
- Ball valve with nozzle locking device
- 180° Swinging Arm



Specifications

BFI Swing Arm Hose Reel 19mm x 36m	HRSO37A
Product	
Code	HRSO37A
STD Hose Length & Diameter	19mm x 36m
Ball Valve (25mm) with Nozzle Interlock	Brass
Ball Valve Handle	M/S Z/P
Wall Bracket / Hose Guide	Mild Steel
Drum Diameter	483mm
Installed Hose reel Depth Off Mount Surface	Approx 310mm
Performance	
Test Pressure	2000kpa
Working Pressure	1500kpa
Minimum Discharge Rate	0.45L/S @ 220kpa

*Installation and commissioning in accordance to AS2441 - 2005

For more information call us on **1800 530 401** or visit **www.bulbeckfire.com.au**